



Maserati Ghibli ECU Removal Guide

FS.MAS.GH.ECU



Estimated Install Time

15 Minutes

Required Tools

Metric Socket Set w/ Ratchet (10mm)
Phillips head screwdriver
Small Flashlight (Optional)

CAUTION

- Always allow car to cool before performing any installation(s) or service(s) on it.
- Always be sure to work on an even and level surface when raising vehicle(s) with a jack, and support all raised vehicles with locked jack stands once elevated.
- Fabspeed Motorsport recommends that all installations be supervised or verified by a trained professional technician.
- Fabspeed Motorsport is not responsible for any personal injury or damage(s) sustained to a vehicle during installation of aftermarket performance parts.


1. Before installing, be sure that the engine is cool. Allow the car to sit for at least one hour after running.
2. Open the hood and locate ECU cover plate on passenger side near the windshield.



3. Remove the two plastic trim clips and pull off the ECU cover.



4. Locate the release lever for the 1st connector and gently lift to release. Proceed to the 2nd connector and remove in similar fashion.



5. Remove the 10mm nut holding the ECU detention bracket allowing the ECU to be removed.



6. Lift the ECU straight up and remove from the vehicle.



7. Safely package up the ECU and send to Fabspeed Motorsport along with the ECU Tuning form with all information filled out so we can promptly tune and return your ECU.
8. Reinstallation of your ECU is the opposite of the previous directions.

If you have any questions, comments, or concerns related to your product, please contact us!